



Wolver UltraTec Longlife III 5W-30

VERPACKUNG

208 L | 60 L | 20 L | 5 L | 4 L | 1 L

WOLVER UltraTec Longlife III SAE 5W30 is a new long-life III synthesis, high-performance, smooth-running engine oil based on the latest technology.

WOLVER UltraTec Longlife III SAE 5W30 was especially developed for the petrol and diesel engines of the VW group, with extended maintenance interval conditions (WIV 3 systems), incl. pump-injector engines.

WOLVER UltraTec Longlife III SAE 5W30 Engine oil of the SAE class 5W/30 is suitable for oil change intervals of up to 50,000 km or 2 years. (See car manufacturer's specifications).

This high performance engine oil can also be used in other types of VW engines, except R5-, V10 TDi pump-injection engines with and without DPF diesel particle filter, which require the VW specifications 503.00, 506.00, 506.01.

SPECIFICATIONS:

SAE 5W-30
API SN/CF/EC
ACEA C3, A3/B4

MEETS THE REQUIREMENTS OF:

VW 504.00/507.00,
VW 502.00/505.00,
501.01/505.00
Porsche A40

Characteristics

- Extreme wear protection
- Excellent viscosity temperature behaviour
- Quick oil feed of critical lubricating points
- Considerable wear reduction on cylinder and camshaft
- High oxidation and temperature stability
- Low volatilization loss
- Very high cleaning capability
- Particularly low emission combustion

Effects

- Reduction of fuel consumption on partial and full load operation as well as reduction of exhaust emission

- Light motor running
- Optimal engine cleanliness
- Very low resistance an motor starting
- Very good operating reliability
- High margin of performance
- Extended oil change intervals
- All-year operation

Utilization

- VW high-performance and normal four-stroke petrol engines motors with and without WIV-systems
- with multivalve-technology
- with turbo charging
- with catalyst technology
- with extended oil change interval
- VW diesel engines with and without WIV-systems
- with pump and nozzle engines
- with diesel particle systems(DPF)
- with turbo charging
- with catalyst technology

Disposal

- **WOLVER UltraTec Longlife III SAE 5W-30** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility

WOLVER UltraTec Longlife III SAE 5W-30 is fully compatible to customary HD oils and can be mixed without any doubts. However, to take full advantage of **WOLVER UltraTec Longlife III SAE 5W-30** it is recommendable to use only **WOLVER UltraTec Longlife III SAE 5W-30** when refilling.

Data table

PROPERTIES	UNIT	TYPICAL INDICATORS
Specific weight at 15°C	kg/m ³	855
Viscosity at -30°C	cP	4730
Viscosity at 40°C	cSt	64,00
Viscosity at 100°C	cSt	11,50
Viscosity index		176
Flash point COC	°C	230
Pour point	°C	-45
TBN	mgKOH/g	6,7
Sulphate ashes	%	0,67