



## Wolver Ultron MS2

### VERPACKUNG

170 KG | 16 KG | 8 KG | 400 ML

**WOLVER ULTRON MS2** - anti-wear lithium grease with molybdenum disulfide (MoS<sub>2</sub>). Suitable for units that operates under extreme heavy and shock loaded conditions or vibrations.

**WOLVER ULTRON MS2** - particularly recommended for application when the vibration destroyed the action of the protective layer and lubrication continuous due to the properties of molybdenum disulfide.

Operating Temperature Range: -30 ° C ... + 130 ° C

### SPECIFICATIONS

NLGI 2 · KPF2K-30 ·  
L-XDCGB 2

### Characteristics

- high anti-wear and extreme pressure properties;
- prolonged protection against water washout and corrosion;
- excellent adhesion to metal and excellent sealing assemblies;
- efficient node work even while considerable decrease of the lubrication layer. Protection against jamming.

### Utilization

- Cardan shafts, fifth wheel couplings, joints and other heavy loaded gear components of cars, trucks, agricultural, quarry and building equipment operating in severe heavy loaded conditions, dust or wet;
- Constant velocity joints (CV joints);
- Heavy industry equipment elements, including mining, lifting appliance (hinges, pins, excavator buckets fastening components, hook suspension cranes, screening mechanisms, highly loaded pillow block bearings, etc.), operating under heavy loaded conditions and vibrations.

### Data table

PROPERTIES	UNIT	TYPICAL INDICATORS
------------	------	--------------------

Viscosity of Oil at 40°C	mm <sup>2</sup> /s	108
Penetration at 25°C	10 <sup>-1</sup> ·mm	280
Dropping point	°C	210
Anti-corrosion properties	-	pass
Weld Load 4-Ball	kg	400
Colour	-	black

208L - Barrel	4234	4260360942341
20L - Pail	4233	4260360942334
10L - Pail	4474	4260360944741
400g -cartridge	4016	4260360940163