



Wolver Universal Gear Oil API GL-4 / GL-5 75W-90

VERPACKUNG

208 L | 20 L | 1 L

Wolver Universal Gear Oil 75W-90 is universal fully synthetic, easy-flowing gear oil. Contains special EP additives for use in heavily loaded gearboxes and other transmissions where EP properties are required.

Wolver Universal Gear Oil 75W-90 - thanks to a special combination of additives, provides high efficiency of the transmission. It has an unusually high resistance to oxidation and to temperature changes.

Wolver Universal Gear Oil 75W-90 - applicable in all vehicles, including commercial vehicles, in all drive systems, synchronized and unsynchronized gearboxes, as well as main gears with or without hypoid gearing and transfer boxes in accordance with the manufacturer's recommendations.

SPECIFICATIONS
SAE 75W-90
API GL-4 / GL-5

MEETS THE REQUIREMENTS OF
MACK GO-j,
MAN 3343 Typ S, 341 E-3/Z-2,
342 M-3
MB 235.0, 235.6, 235.8,
SCANIA STO 1:0,
VOLVO 97310, 1273.10, 1273.12,
ZF TE-ML 01, 02B, 05A, 07A, 08, 12A, 16B,
C, D,F, 17B, 19B
MT-1
MIL-L-2105D
PRF-2105E

Properties:

- Excellent EP properties;
- Extreme wear resistance;
- Excellent resistance to oxidation;
- Exceptional viscosity-temperature characteristics;
- High resistance to compression;
- Protection against corrosion;
- Prevents foaming;

- Neutral with respect to sealing materials.

Efficiency

- Provides fuel economy;
- Optimum working properties;
- Extended service life;
- Excellent fluidity in the cold, down to -45 ° C;
- Year-round use;
- Universal application.

Application

- Manual gearbox and differentials;
- Cars and trucks, light vans and four-wheel drive vehicles;
- Agriculture, construction and working machinery

Waste management

Used oil **Wolver Universal Gear Oil 75W-90** refers to waste of the 2nd category and must be disposed of in specially designated places.

Compatibility

Wolver Universal Gear Oil 75W-90 is compatible with comparable oils and can be mixed with any of them. In order to take full advantage of Wolver Universal Gear Oil 75 W-90, it is recommended to use it without mixing.

Data table

PROPERTIES	UNIT	TYPICAL INDICATORS
Specific weight at 15°C	kg/m ³	873
Viscosity at 40°C	cSt	93
Viscosity at 100°C	cSt	14.8
Viscosity index		164
Flash point COC	°C	198
Pour point	°C	-45